

Lift it up, Tie it down, Pull it around

Eye & Eye Web Sling Ratings (T3 & T4)

Eye & Eye web slings can be used in vertical, choker or basket hitches and have a fixed eye on each end. All sizes come standard with wear-pad in the eyes, 2" and wider come standard with tapered eyes.



Single Ply Type 3 & 4 Slings



Material Width [in]	Stock Code	Eye Dimensions		Working Load Limit [lbs]					Min Length [ft]	Weight	
		Width	Length	Vertical 90°	120° Choke	90° Basket	60° Basket	45° Basket		10ft Sling	per ft
1"	EE1 901	1"	9"	1,600	1,250	3,200	2,750	2,250	4	0.77	0.05
2"	EE1 902	2"	12"	3,100	2,450	6,200	5,350	4,350	4	1.56	0.11
3"	EE1 903	1-1/2"	12"	4,700	3,750	9,400	8,100	6,600	4	2.65	0.18
4"	EE1 904	1-1/2"	14"	6,200	4,950	12,400	10,700	8,750	5	3.30	0.22
6"	EE1 906	2"	24"	9,300	7,400	18,600	16,100	13,150	8	4.85	0.32
8"	EE1 908	3"	24"	11,800	9,400	23,600	20,400	16,650	8	7.17	0.45
10"	EE1 910	3-1/2"	24"	14,700	11,750	29,400	25,450	20,750	8	9.38	0.60
12"	EE1 912	4"	30"	17,600	14,050	35,200	30,450	24,850	10	11.52	0.73

Double Ply Type 3 & 4 Slings



Material Width [in]	Stock Code	Eye Dimensions		Working Load Limit [lbs]					Min Length [ft]	Weight	
		Width	Length	Vertical 90°	120° Choke	90° Basket	60° Basket	45° Basket		10ft Sling	per ft
1"	EE2 901	1"	9"	3,100	2,450	6,200	5,350	4,350	3	1.22	0.11
2"	EE2 902	2"	12"	6,200	4,950	12,400	10,700	8,750	4	2.46	0.22
3"	EE2 903	1-1/2"	12"	8,800	7,000	17,600	15,200	12,400	4	3.94	0.35
4"	EE2 904	1-1/2"	14"	11,000	8,800	22,000	19,050	15,550	5	4.84	0.44
6"	EE2 906	2"	24"	16,500	13,200	33,000	28,550	23,300	8	7.13	0.66
8"	EE2 908	3"	24"	22,700	18,150	45,400	39,300	32,100	8	10.31	0.91
10"	EE2 910	3-1/2"	24"	28,400	22,700	56,800	49,150	40,150	8	13.47	1.18
12"	EE2 912	4"	30"	34,100	27,250	68,200	59,050	48,200	10	16.56	1.45

Four-Ply Type 3 & 4 Slings



Material Width [in]	Stock Code	Eye Dimensions		Working Load Limit [lbs]					Min Length [ft]	Weight	
		Width	Length	Vertical 90°	120° Choke	90° Basket	60° Basket	45° Basket		10ft Sling	per ft
1"	EE4 901	1"	12"	5,500	4,400	11,000	9,500	7,750	4	2.51	0.22
2"	EE4 902	2"	12"	11,000	8,800	22,000	19,050	15,550	4	4.94	0.40
3"	EE4 903	1-1/2"	18"	16,400	13,100	32,800	28,400	23,150	5	8.00	0.71
4"	EE4 904	2"	18"	20,400	16,300	40,800	35,300	28,850	6	10.12	0.89
6"	EE4 906	3"	24"	30,600	24,450	61,200	53,000	43,250	8	14.91	1.31
8"	EE4 908	4"	24"	CONTACT SUPER SLINGS					8	21.05	1.81
10"	EE4 910	5"	30"						10	27.53	2.36
12"	EE4 912	6"	36"						12	34.56	2.91



NEVER EXCEED THE WORKING LOAD LIMIT.
ALWAYS CHECK THE IDENTIFICATION TAG TO DETERMINE THE SLINGS RATED CAPACITY IS APPROPRIATE FOR THE APPLICATION. RATINGS LISTED ARE VALID FOR NEW SLINGS ONLY. ALWAYS INSPECT BEFORE USE

Sling Protection
Web Slings
Round Slings
Synthetic Chain Slings
Wire Rope Slings
Chain Slings
Shackles & Turnbuckles
Hooks & Links
Lifting Points
Hoists & Blocks
Lifting Devices
Pipe & Hose Restraints
Tie Down Assemblies
Tie Down Accessories
Towing & Recovery
Rope & Carriage