

Sling Protection  
Web Slings  
Round Slings  
Synthetic Chain Slings  
Wire Rope Slings  
Chain Slings  
Shackles & Turnbuckles  
Hooks & Links  
Lifting Points  
Hoists & Blocks  
Lifting Devices  
Pipe & Hose Restraints  
Tie Down Assemblies  
Tie Down Accessories  
Towing & Recovery  
Rope & Cordage

### Endless Web Sling Ratings

Endless web slings can be used in vertical, choker or basket hitches. The wear point on an endless sling can be rotated for longer lifespan.



### Single-Ply Type 5 Slings



Material Width [in]	Stock Code	Working Load Limit (lbs)					Min Length [ft]	Weight	
		Vertical 90°	120° Choke	90° Basket	60° Basket	45° Basket		10ft Sling	per ft
1"	EN1 901	3,200	2,550	6,400	5,500	4,500	2	1.17	0.11
2"	EN1 902	6,200	4,950	12,400	10,700	8,750	2	2.34	0.22
3"	EN1 903	9,400	7,500	18,800	16,250	13,250	2	3.69	0.35
4"	EN1 904	12,400	9,900	24,800	21,450	17,500	3	4.62	0.44
6"	EN1 906	18,600	14,850	37,200	32,200	26,300	3	6.79	0.65
8"	EN1 908	21,200	16,950	42,400	36,700	29,950	3	9.42	0.91
10"	EN1 910	26,500	21,200	53,000	45,850	37,450	3	12.3	1.18
12"	EN1 912	31,800	25,400	63,600	55,050	44,950	3	15.12	1.45

### Double-Ply Type 5 Slings



Material Width [in]	Stock Code	Working Load Limit (lbs)					Min Length [ft]	Weight	
		Vertical 90°	120° Choke	90° Basket	60° Basket	45° Basket		10ft Sling	per ft
1"	EN2 901	6,200	4,950	12,400	10,700	8,750	2	2.4	0.22
2"	EN2 902	12,400	9,900	24,800	21,450	17,500	2	4.8	0.44
3"	EN2 903	17,600	14,050	35,200	30,450	24,850	2	7.56	0.71
4"	EN2 904	22,000	17,600	44,000	38,100	31,100	3	9.46	0.89
6"	EN2 906	33,000	26,400	66,000	57,150	46,650	3	13.92	1.30
8"	EN2 908	42,300	33,800	84,600	73,250	59,800	4	19.26	1.81
10"	EN2 910	52,900	42,300	105,800	91,600	74,800	4	25.19	2.36
12"	EN2 912	63,500	50,800	127,000	109,950	89,800	5	30.96	2.91

### Four-Ply Type 5 Slings



Material Width [in]	Stock Code	Working Load Limit (lbs)					Min Length [ft]	Weight	
		Vertical 90°	120° Choke	90° Basket	60° Basket	45° Basket		10ft Sling	per ft
1"	EN4 901	11,000	8,800	22,000	19,050	15,550	3	4.72	0.40
2"	EN4 902	22,000	17,600	44,000	38,100	31,100	4	9.73	0.90
3"	EN4 903	32,900	26,300	65,800	56,950	46,500	4	15.3	1.41
4"	EN4 904	40,800	32,600	81,600	70,650	57,700	4	19.14	1.78
6"	EN4 906	61,200	48,950	122,400	106,000	86,550	5	28.18	2.61
8"	EN4 908	CONTACT SUPER SLINGS					8	21.05	1.81
10"	EN4 910						10	27.53	2.36
12"	EN4 912						12	34.56	2.91



**NEVER EXCEED THE WORKING LOAD LIMIT.**  
ALWAYS CHECK THE IDENTIFICATION TAG TO DETERMINE THE SLINGS RATED CAPACITY IS APPROPRIATE FOR THE APPLICATION. RATINGS LISTED ARE VALID FOR NEW SLINGS ONLY. ALWAYS INSPECT BEFORE USE