

Lift it up, Tie it down, Pull it around

Reverse(Return) Eye Web Sling Ratings

Reverse Eye Slings are extremely durable slings that feature full body and eye wear pads. Eyes are twisted 90° to the sling body for tighter choker hitches and easy vertical and basket hitch rigging.



Single Ply Type 6 & 7 Slings

Material Width	Stock Code	Eye Dimensions		Working Load Limit [lbs]					Min Length	Weight	
		Width	Length	Vertical 90°	120° Choke	90° Basket	60° Basket	45° Basket		[ft]	10ft Sling
[in]											
2"	RE1 901	1"	9"	2,500	3,200	6,400	5,540	4,520	3	2.21	0.21
4"	RE1 902	1"	12"	5,000	6,400	12,800	11,080	9,050	4	4.02	0.40
6"	RE1 903	1-1/2"	12"	7,600	9,600	19,200	16,630	13,570	5	6.41	0.64



Double-Ply Type 6 & 7 Slings

Material Width	Stock Code	Eye Dimensions		Working Load Limit [lbs]					Min Length	Weight	
		Width	Length	Vertical 90°	120° Choke	90° Basket	60° Basket	45° Basket		[ft]	10ft Sling
[in]											
2"	RE2 901	1"	12"	5,000	6,400	12,800	11,080	9,050	4	3.44	0.32
4"	RE2 902	2"	18"	9,000	11,400	22,800	19,740	16,120	6	6.84	0.63
6"	RE2 903	1-1/2"	18"	13,000	17,000	34,000	29,440	24,040	6	10.28	0.99

Wide Body Web Sling Ratings

Wide Body Web Slings are specifically designed for use in basket hitches where a larger surface area is required for load stability or for proper handling of fragile or highly finished surfaces. Eyes of slings are tapered to better fit in hoist or crane hooks.



Double Ply Wide Body Cargo Slings Type 8

Material Width	Stock Code	Eye Dimensions		Working Load Limit [lbs]			Min Length	Weight	
		Width	Length	90° Basket	60° Basket	45° Basket		[ft]	10ft Sling
[in]									
6"	WB2 903	1-1/2"	12"	18,800	16,200	13,200	4	5	0.44
8"	WB2 904	1-1/2"	12"	24,800	21,400	17,500	4	6.08	0.53
12"	WB2 906	2"	16"	37,200	32,200	26,300	6	9.06	0.81
16"	WB2 908	3"	20"	47,200	40,800	33,300	7	12.87	1.07
20"	WB2 910	3-1/2"	24"	58,800	50,900	41,500	8	17.58	1.35
24"	WB2 912	4"	30"	70,400	60,900	49,700	10	20.96	1.62




NEVER EXCEED THE WORKING LOAD LIMIT.
 ALWAYS CHECK THE IDENTIFICATION TAG TO DETERMINE THE SLINGS RATED CAPACITY IS APPROPRIATE FOR THE APPLICATION. RATINGS LISTED ARE VALID FOR NEW SLINGS ONLY. ALWAYS INSPECT BEFORE USE

- Web Slings
- Round Slings
- Synthetic Chain Slings
- Wire Rope Slings
- Chain Slings
- Shackles & Turnbuckles
- Hooks & Links
- Lifting Points
- Hoists & Blocks
- Lifting Devices
- Pipe & Hose Restraints
- Tie Down Assemblies
- Tie Down Accessories
- Towing & Recovery
- Rope & Carriage

Attached Eye Web Sling Ratings

Attached Eye Web Slings are specifically designed for use in basket hitches where a larger surface area is required for load stability or for proper handling of fragile or highly finished surfaces. Eyes of slings are tapered to better fit in hoist or crane hooks.



Single Ply Attached-Eye Wide Body Slings Type 9

Material Width [in]	Stock Code	Eye Dimensions		Working Load Limit (lbs)			Min Length [ft]	Weight	
		Width	Length	90° Basket	60° Basket	45° Basket		10ft Sling	per ft
6"	WB2 903	1-1/2"	12"	18,800	16,200	13,200	4	5	0.44
8"	WB2 904	1-1/2"	12"	24,800	21,400	17,500	4	6.08	0.53
12"	WB2 906	2"	16"	37,200	32,200	26,300	6	9.06	0.81
16"	WB2 908	3"	20"	47,200	40,800	33,300	7	12.87	1.07
20"	WB2 910	3-1/2"	24"	58,800	50,900	41,500	8	17.58	1.35
24"	WB2 912	4"	30"	70,400	60,900	49,700	10	20.96	1.62



Single Ply Attached-Eye Wide Body Slings Type 9

Material Width [in]	Stock Code	Eye Dimensions		Working Load Limit (lbs)			Min Length [ft]	Weight	
		Width	Length	90° Basket	60° Basket	45° Basket		10ft Sling	per ft
6"	WB2 903	1-1/2"	12"	18,800	16,200	13,200	4	5	0.44
8"	WB2 904	1-1/2"	12"	24,800	21,400	17,500	4	6.08	0.53
12"	WB2 906	2"	16"	37,200	32,200	26,300	6	9.06	0.81
16"	WB2 908	3"	20"	47,200	40,800	33,300	7	12.87	1.07
20"	WB2 910	3-1/2"	24"	58,800	50,900	41,500	8	17.58	1.35
24"	WB2 912	4"	30"	70,400	60,900	49,700	10	20.96	1.62

Custom Web Sling Assemblies

Custom is our specialty. Over the years we have manufactured all types of custom web slings assemblies, including, pail lifters, drum lifters, tool bag slings, transformer slings, cylinder lifters and many more. Contact your Super Slings representative with your custom requirements.



WARNING! NEVER EXCEED THE WORKING LOAD LIMIT. ALWAYS CHECK THE IDENTIFICATION TAG TO DETERMINE THE SLINGS RATED CAPACITY IS APPROPRIATE FOR THE APPLICATION. RATINGS LISTED ARE VALID FOR NEW SLINGS ONLY. ALWAYS INSPECT BEFORE USE

Sling Protection
Web Slings
Round Slings
Synthetic Chain Slings
Wire Rope Slings
Chain Slings
Shackles & Turnbuckles
Hooks & Links
Lifting Points
Hoists & Blocks
Lifting Devices
Pipe & Hose Restraints
Tie Down Assemblies
Tie Down Accessories
Towing & Recovery
Rope & Cordage